Safety Data Sheet

according to Regulation (EC) No. 2015/830 Date:8/27/2015 Supersedes:3/6/2015

Version: 9.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : TIPP-EX® RAPID

Type of product : Correction fluid

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Correction fluid

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SOCIETE BIC

14, Rue Jeanne d'Asnières 92611 CLICHY Cédex

T+33 01 45 19 52 00 - F+33 01 45 19 52 99

Bic.Contact@bicworld.com

1.4. Emergency telephone number

| Country | Organisation/Company | Address | Emergency number |
|----------------|--|---------------------------------|------------------|
| United Kingdom | Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust | Avonley Road SE14 5ER London | 0870 243 2241 |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411

Full text of classification categories and H statements: see section 16

Adverse physicochemical, human health and environmental effects

: Highly flammable liquid and vapour. Causes skin irritation. Vapours may cause drowsiness and dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

IS02

GHS09

Signal word (CLP) : Danger

Hazardous ingredients : Naphtha (petroleum), hydrotreated light
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) : P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P273 - Avoid release to the environment

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P261 - Avoid breathing vapours

9/1/2015 EN (English) 1/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

Reduced labelling allowed for small packaging (<125 ml)

Hazard pictograms (CLP)







GHS02

Signal word (CLP) : Danger

Hazard statements (CLP) : H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) : P261 - Avoid breathing vapours

Hazardous ingredients : Naphtha (petroleum), hydrotreated light

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|------|--|
| Titanium dioxide | (CAS No) 13463-67-7 (EC no) 236-675-5 | < 50 | Not classified |
| Naphtha (petroleum), hydrotreated light | (CAS No) 64742-49-0 (EC no) 265-151-9 (EC index no) 649-328-00-1 | < 40 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| Naphtha (petroleum), light alkylate | (CAS No) 64741-66-8 (EC no) 265-068-8 (EC index no) 649-276-00-X | < 10 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| Solvent naphtha (petroleum), light aromatic | (CAS No) 064742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 | < 1 | Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304 |
| carbon black substance with national workplace exposure limit(s) (GB) | (CAS No) 1333-86-4 (EC no) 215-609-9 | < 1 | Not classified |
| Solvent naphtha (petroleum), medium aliphatic | (CAS No) 064742-88-7 (EC no) 265-191-7 (EC index no) 649-405-00-X | <1 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If the person

feels unwell : Seek medical advice.

First-aid measures after skin contact : Wash immediately with plenty of soap and water. Obtain medical attention if pain, blinking or

redness persist.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If

irritation persists, consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Seek medical advice (show the label where possible).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Drowsiness. Dizziness.

Symptoms/injuries after skin contact : Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO2).

9/1/2015 EN (English) 2/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

5.2. Special hazards arising from the substance or mixture

Fire hazard : On heating or during combustion : Toxic vapours may be released.

Explosion hazard : The vapours are denser than air and may travel along the ground. Distance ignition possible.

5.3. Advice for firefighters

Precautionary measures fire

: Evacuate the danger area. Cool down the containers exposed to heat with a water spray. Contain the extinguishing fluids by bunding (the product is hazardous for the environment). Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Avoid contact with skin and eyes. Do not breathe smoke. No flames, no sparks. Eliminate all sources of ignition. No smoking. In case of important spillage: Mark out the contaminated area with signs and prevent access to unauthorized personnel. Prevent the product from entering drains or confined areas. Ventilate spillage area. Stop leak if safe to do so. Use only non-sparking tools.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Contain the spilled material by bunding (product is hazardous for the environment). Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

For containment

: Absorb spillage with: inert absorbent material. Sand/earth.

Methods for cleaning up

: Sweep up or vacuum up the product. Dispose of contaminated materials in accordance with

current regulations.

6.4. Reference to other sections

For further information refer to section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Vapour exhaust preferably at emission point. Use non-sparking tools. Avoid contact with skin and eyes. Do not breathe smoke. No flames, no sparks. Eliminate all sources of ignition. Smoking is forbidden. Take precautionary measures against static discharges. Do not overheat the product.

Hygiene measures

: Do not drink, eat or smoke in the workplace. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: The floor of the depot must be impermeable, non-combustible and designed to form a basin, in order that stored flammable liquids should not, under any circumstances, be released outside.

Storage conditions

: Store in a cool, well-ventilated place. Keep container tightly closed. Avoid ignition sources. Keep away from naked flames/heat.

Incompatible materials

: Strong oxidizing agents. Oxidizing materials.

Packaging materials : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Titanium dioxide (13463-67-7) | | |
|-------------------------------|------------------|--|
| United Kingdom | Local name | Titanium dioxide |
| United Kingdom | WEL TWA (mg/m³) | 4 mg/m³ respirable 10 mg/m³ total inhalable |
| carbon black (1333-86 | -4) | |
| United Kingdom | Local name | Carbon black |
| United Kingdom | WEL TWA (mg/m³) | 3.5 mg/m³ |
| United Kingdom | WEL STEL (mg/m³) | 7 mg/m³ |

8.2. Exposure controls

Technical measures : Ensure good ventilation of the work station. Extraction to remove vapours at their source.

9/1/2015 EN (English) 3/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

Hand protection : Impermeable protective gloves. The protective gloves to be used must comply with the

specifications of EC directive 89/686/EEC and the resultant standard EN 374. Breakthrough

time: refer to the recommendations of the supplier

Eye protection : Safety glasses

Respiratory protection : If vapour is released : Aerosol filter type : A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : white.
Odour : Solvent.

Odour threshold : No data available
pH : Not applicable
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 95 - 114 °C (760 mmHg)

Flash point : -9 °C (NF EN ISO 13736)

Auto-ignition temperature : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapour pressure : 26 - 49 mm Hg (20 °C)

Relative vapour density at 20 °C : No data available

Relative density : 1.25 (25°C)

Solubility : Water: 0.1 g/l Practically insoluble

Log Pow : No data available
Viscosity, kinematic : > 60 mm²/s (40°C)
Viscosity, dynamic : No data available
Explosive properties : No data available

Oxidising properties : Non oxidizing material according to EC criteria.

Explosive limits : 1.7 - 12.3 vol %

9.2. Other information

Additional information : Volatile component : 0.89 - 1.08 %

SECTION 10: Stability and reactivity

10.1. Reactivity

To our knowledge, the product does not present any particular risk, under normal conditions of use.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

None to our knowledge.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Ignition sources.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

On combustion or on thermal decomposition (pyrolysis) releases: Carbon oxides (CO, CO2). Various hydrocarbon fragments.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

| Naphtha (petroleum), light alkylate (64741-66-8) | |
|--|---------------|
| LD50 oral rat | > 7000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (ppm) | > 5.04 ppm/4h |

9/1/2015 EN (English) 4/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

| Naphtha (petroleum), hydrotreated light (64742-49-0) | | |
|--|--|--|
| LD50 oral rat | > 5000 mg/kg | |
| LD50 dermal rabbit | 3160 mg/kg | |
| LC50 inhalation rat (mg/l) | > 12 mg/l/6h | |
| Titanium dioxide (13463-67-7) | | |
| LD50 oral rat | > 5000 mg/kg (OECD 425 method) | |
| LD50 dermal rabbit | > 10000 mg/kg | |
| LC50 inhalation rat (mg/l) | > 3.56 mg/l/4h | |
| Skin corrosion/irritation | : Causes skin irritation. | |
| | pH: Not applicable | |
| Serious eye damage/irritation | : Not classified (Based on available data, the classification criteria are not met) | |
| | pH: Not applicable | |
| Respiratory or skin sensitisation | : Not classified (Based on available data, the classification criteria are not met) | |
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met) | |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met) | |
| | Titanium dioxide (powder) is listed as being potentially carcinogenic (group 2B) by the CIRC, based on studies on animals | |
| | However, studies on human epidemiology do not suggest links between the occupational exposure to titanium dioxide and the risk of cancer | |
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met) | |
| Specific target organ toxicity (single exposure) | : May cause drowsiness or dizziness. | |
| Specific target organ toxicity (repeated exposure) | : Not classified (Based on available data, the classification criteria are not met) | |
| Aspiration hazard | : Not classified (Based on available data, the classification criteria are not met) | |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| Naphtha (petroleum), light alkylate (64741-66-8) | | |
|--|--|--|
| LC50 fish 1 8.3 mg/l/96h (Pimephales promelas) | | |
| Naphtha (petroleum), hydrotreated light (64742-49-0) | | |
| EC50 Daphnia 2.6 mg/l (crustacean) | | |

12.2. Persistence and degradability

| TIPP-EX® RAPID | |
|-------------------------------|--|
| Persistence and degradability | Mixture based on substances which are not readily biodegradable. |

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Discharging into rivers and drains is forbidden. Dispose of in accordance with relevant local

regulations. Destroy at an authorised site.

Additional information : The user's attention is drawn to the possible existence of specific european, national or local

regulations regarding disposal.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | | IMDG | IATA |
|-------|-----------|------|------|
| 14.1. | UN number | | |
| 1139 | | 1139 | 1139 |

9/1/2015 EN (English) 5/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

| ADR | IMDG | IATA |
|---|---|--|
| 14.2. UN proper shipping name | | |
| COATING SOLUTION | COATING SOLUTION | COATING SOLUTION |
| Transport document description | | |
| UN 1139 COATING SOLUTION, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS | UN 1139 COATING SOLUTION, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS | |
| 14.3. Transport hazard class(es) | | |
| 3 | 3 | 3 |
| 3 | 1 | ************************************** |
| 14.4. Packing group | | |
| II | II | II |
| 14.5. Environmental hazards | | |
| Dangerous for the environment : Yes | Dangerous for the environment : Yes Marine pollutant : Yes | Dangerous for the environment : Yes |

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1 Special provisions (ADR) : 640D Limited quantities (ADR) : 51 Excepted quantities (ADR) : E2

: P001, IBC02, R001 Packing instructions (ADR)

: MP19 Mixed packing provisions (ADR) Portable tank and bulk container instructions : T4 (ADR)

Portable tank and bulk container special

provisions (ADR) Tank code (ADR) : LGBF Vehicle for tank carriage : FL Transport category (ADR) : 2 : S2, S20 Special provisions for carriage - Operation

(ADR)

Hazard identification number (Kemler No.) : 33

Orange plates

33

: TP1, TP8

Tunnel restriction code (ADR) : D/E EAC code : •3YE

- Transport by sea

Limited quantities (IMDG) : 5 L Limited quantities (IMDG) : 5L Excepted quantities (IMDG) : E2 Packing instructions (IMDG) : P001 : IBC02 IBC packing instructions (IMDG) Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1, TP8 : F-E EmS-No. (Fire) EmS-No. (Spillage) : S-E Stowage category (IMDG) : B MFAG-No : 127;128

- Air transport

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341

9/1/2015 EN (English) 6/7

Safety Data Sheet

according to Regulation (EC) No. 2015/830

PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

This sheet was updated (refer to the date at the top of this page). (see section(s): 3, 8).

Other information

: No experimental study is available on the mixture. Information hereunder are based on our knowledge on components, and classification of the mixture is determined with the calculation method.

Safety data sheet established by : LISAM SERVICES - TELEGIS

Rue de la Couture F-60400 PASSEL Safety Made Easy with www.lisam.com.

Full text of H- and EUH-statements:

| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |
|-------------------|--|
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Carc. 1B | Carcinogenicity, Category 1B |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Muta. 1B | Germ cell mutagenicity, Category 1B |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H336 | May cause drowsiness or dizziness |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H411 | Toxic to aquatic life with long lasting effects |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

9/1/2015 EN (English) 7/7