

Telefax: +43 (0)-7717-8053-4344



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

#### **GRIP Marker Permanent BLACK 13/2399**

Product code: 100-008-696 Print date: 23.10.2015 Page 1 of 9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

GRIP Marker Permanent BLACK 13/2399

### Further trade names

Recipe No.: 13/2399

Included in

- Permanent Marker 150399 / 150499

- Permanent Marker Refill 150599

- Multimark permanent 151399, 152399, 152599

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Ink

### 1.3. Details of the supplier of the safety data sheet

Company name: A.W. Faber-Castell Ges.m.b.H

Österreich

Street: Saag 7

Place: A-4090 Engelhartszell +43 (0)-7717-8053-0 Telephone:

Contact person: Dr. Gerhard Lugert

Gerhard.Lugert@faber-castell.de e-mail:

Faber-Castell AG Responsible Department:

> Nürnberger Str. 2 D-90546 Stein Abtlg. TEC

Dr. Gerhard Lugert, +49 (0) -911-9965 5550, privat: +49 (0)-911-61 64 26

Wolfgang Schwarz, +49 (0) -911-9965 5878

1.4. Emergency telephone +49 (0) -911-9965 5550

number: +49 (0) -911-61 64 26

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazard Statements:

Highly flammable liquid and vapour.

# 2.2. Label elements

# Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



### **Hazard statements**

H225 Highly flammable liquid and vapour.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.



according to Regulation (EC) No 1907/2006

since 1/61	200000000000000000000000000000000000000						
GRIP Marker Permanent BLACK 13/2399							
Print date: 23.10.2015	Product code: 100-008-696	Page 2 of 9					
P233	Keep container tightly closed.						
P240	Ground/bond container and receiving equipment.						
P241	Use explosion-proof electrical/ventilating/lighting equipment.						
P242	Use only non-sparking tools.						
P243	Take precautionary measures against static discharge.						
P280	Wear protective gloves/protective clothing/eye protection/face protection.						
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.						
P370+P378	In case of fire: Use Water. Carbon dioxide (CO2). Dry chemical. to extinguish.						
P403+P235	Store in a well-ventilated place. Keep cool.						
2.3. Other hazards							

#### 2.3. Other nazards

No data.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Chemical characterization

Alcohol-based inks with dyestuff and additives.

### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according	to Regulation (EC) No. 1272/2008 [C	LP]		
64-17-5	ethanol, ethyl alcohol				
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2; H225				
107-98-2	1-methoxy-2-propanol; r	15 - < 20 %			
	203-539-1	603-064-00-3	01-2119457435-35		
	Flam. Liq. 3, STOT SE 3; H226 H336				
143-07-7	lauric acid				
	205-582-1				
	Eye Irrit. 2; H319				

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

Show this safety data to the medicating physician.

#### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### After contact with skin

Wash with warm water and soap. Change contaminated clothing.

### After contact with eyes

Wash eyes when eyelid opened with soft and clean water for 15 minutes. Call an oculist, particularly if redness, pain or visual impairment occur.

### After ingestion

Rinse mouth immediately and drink plenty of water. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).





according to Regulation (EC) No 1907/2006

#### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 3 of 9

#### 4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data.

#### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water. Carbon dioxide (CO2). Dry chemical. Sand.

### Unsuitable extinguishing media

For this substance / preparation no extinguishing agent restriction exist.

### 5.2. Special hazards arising from the substance or mixture

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical resistant suit. Water spray may be used to cool closed containers. Heating causes rise in pressure with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and clothes. Avoid contact with skin. Change contaminated clothing. Wear personal protection equipment. Keep away unguarded persons. Remove all sources of ignition. Provide adequate ventilation.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Information for safe handling, see section 7.

Information for personal protectice equipment, see section 8.

Information for disposal, see section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

Avoid contact with skin and clothes. Avoid contact with skin. Change contaminated clothing. Keep container tightly closed. Secure an adequate ventilation. Emergency eye showers should be directly close-by.

### Advice on protection against fire and explosion

Avoid sparks, flames and electrostatic charging. Use only non-sparking tools. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

#### Further information on handling

Keep away from food, beverages and feeding stuff. Do no eat, drink or smoke when using this product. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.



according to Regulation (EC) No 1907/2006

#### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 4 of 9

Recommended storage temperatur: 5 - 35 °C

#### Advice on storage compatibility

Store separated from oxidizing agents. Keep away from food, beverages and feeding stuff.

### Further information on storage conditions

Protect against: heat.

#### 7.3. Specific end use(s)

No data.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

#### Additional advice on limit values

Keep away fire.

### 8.2. Exposure controls

# Appropriate engineering controls

Additional information: TA-Luft: Klasse III

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

## Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

### Eye/face protection

Wear eye/face protection.

#### Hand protection

Solvent-resistant gloves (PVA/H4).

### Skin protection

Body protection must be chosen depending on activity and possible exposure, eg Apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

### Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

#### **Environmental exposure controls**

Do not allow the product to enter the drains. Do not discharge into the subsoil / soil.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: black
Odour: alcoholic

Test method



according to Regulation (EC) No 1907/2006

GRIP Marker Permanent BLACK 13/2399					
Print date: 23.10.2015	Product code: 100-008-696	Page 5 of 9			
pH-Value:	No data.				
Changes in the physical state					
Melting point:	<-20 °C				
Initial boiling point and boiling range:	78 °C				
Sublimation point:	No data.				
Softening point:	No data.				
Pour point:	No data.				
:	No data.				
Flash point:	12 °C				
Sustaining combustion:	Sustaining combustion				
Flammability					
Solid:	No data.				
Gas:	No data.				
Explosive properties  Vapours may form explosive mixtures with the second control of the	th air.				
Lower explosion limits:	1,8 vol. %				
Upper explosion limits:	15 vol. %				
Ignition temperature:	270 °C				
Auto-ignition temperature					
Solid:	No data.				
Gas:	No data.				
Decomposition temperature:	No data.				
Oxidizing properties  Non-oxidizing.					
Vapour pressure:	58 hPa				
(at 20 °C) Vapour pressure:	293 hPa				
(at 50 °C)	255 111 4				
Density (at 20 °C):	ca. 1 g/cm³				
Bulk density:	No data.				
Water solubility:	miscible.				
Solubility in other solvents  Miscible with: Ethanol. Water.					
Partition coefficient:	No data.				
Viscosity / dynamic: (at 20 °C)	5,1 mPa⋅s				
Viscosity / kinematic:	No data.				
Flow time:	No data.				
Vapour density:	No data.				
Evaporation rate:	No data.				
Solvent separation test:	No data.				
Solvent content:	71,74 %				
9.2. Other information	, /				
Solid content:	25,00 %				
Cond Contont.	25,00 /0				



according to Regulation (EC) No 1907/2006

### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 6 of 9

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data.

### 10.2. Chemical stability

No decomposition, if the regulations/references for storage and handling are respected.

# 10.3. Possibility of hazardous reactions

No data.

# 10.4. Conditions to avoid

Avoid sparks, flames and electrostatic charging.

### 10.5. Incompatible materials

Alkali metals. Alkaline earth metals. strong oxidizers

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2).

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Acute toxicity**

CAS No	Chemical name							
	Exposure routes	Method	Dose	Species	Source			
64-17-5	ethanol, ethyl alcohol							
	oral	LD50	6200 mg/kg	Ratte	IUCLID			
	inhalative (4 h) vapour	LC50	95,6 mg/l	Ratte	RTECS			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether							
	oral	LD50	> 5000 mg/kg	Ratte	IUCLID			
	dermal	LD50	11000 mg/kg	Kaninchen				

# Irritation and corrosivity

Primary irritation:

Irritant effect on the skin: none known

Irritant effect on the eye: Slight irritation possible

# **SECTION 12: Ecological information**

### 12.1. Toxicity

CAS No	Chemical name								
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source			
64-17-5	ethanol, ethyl alcohol								
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether								
	Acute fish toxicity	LC50 mg/l	4600 - 10000	96 h	Leuciscus idus	IUCLID			
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Selenastrum capricornutum				
	Acute crustacea toxicity	EC50	> 500 mg/l	48 h	Daphnia magna	IUCLID			

### 12.2. Persistence and degradability



according to Regulation (EC) No 1907/2006

### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 7 of 9

No data.

### 12.3. Bioaccumulative potential

No data.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

### 12.4. Mobility in soil

No data.

### 12.5. Results of PBT and vPvB assessment

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No data.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

### Advice on disposal

Waste disposal according to official state regulations and local regulations.

German Waste Catalogue - Waste code: 80102

Disposal identification: Colours without halogenated solvents. Alcohol-based inks.

# Contaminated packaging

Clean with ethanol. Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number:** UN 1210

14.2. UN proper shipping name: PRINTING INK flammable

14.3. Transport hazard class(es): 3 14.4. Packing group: П Hazard label: 3 Classification code: F1 **Special Provisions:** 163 640C Limited quantity: 5 L Transport category: 2 Hazard No: 33 Tunnel restriction code: D/F

### Other applicable information (land transport)

E2

# Inland waterways transport (ADN)

**14.1. UN number:** UN 1210

14.2. UN proper shipping name: PRINTING INK flammable

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 163 640C



according to Regulation (EC) No 1907/2006

### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 8 of 9

Limited quantity: 5 L

Other applicable information (inland waterways transport)

F2

Marine transport (IMDG)

**14.1. UN number:** UN 1210

14.2. UN proper shipping name: PRINTING INK flammable

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:163Limited quantity:5 LEmS:F-E. S-D

Other applicable information (marine transport)

E2

Air transport (ICAO)

**14.1. UN number:** UN 1210

14.2. UN proper shipping name: PRINTING INK flammable

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3 A72Limited quantity Passenger:1 L

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

Passenger-LQ: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data.

Other applicable information

The transport regulations are cited according to international regulations and in the form applicable in Germany (GGVSE). Possible national deviations in other countries are not considered.

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

2010/75/EU (VOC): 71,78 % (717,8 g/l) 2004/42/EC (VOC): 71,78 % (717,8 g/l)

**National regulatory information** 

Water contaminating class (D): 2 - water contaminating





according to Regulation (EC) No 1907/2006

### **GRIP Marker Permanent BLACK 13/2399**

Print date: 23.10.2015 Product code: 100-008-696 Page 9 of 9

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

### **Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)