Product Name: Cartridge for V BOARD MASTER

SAFETY DATA SHEET

Date of Issue: November 01, 2016

SDS No.: RI-023 Version: 008



Page 1/7

SDS No.:RI-023

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

For ink unless otherwise specified.

1.1. Product identifier.

Product name : Cartridge for V BOARD MASTER

Product code : WBS-VBM-B/R/L/G/O/V

Mixture name : WMAM-B/L/G/V, WMA-R/O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses :Ink for writing instrument

1.3. Details of the supplier of the safety data sheet

Name of manufacture

: PILOT CORPORATION OF EUROPE

/ supplier

Address : PAE de la Caille 74350 ALLONZIER-LA-CAILLE (France)

Telephone number : +33 (0)4 50 08 33 00

Working hours (from 8.30am to 12.30pm and from 01.30pm to 05.30pm

:04.00pm on Friday-French time)

Facsimile number : +33 (0)4 50 46 43 59

E-mail address : pilotfrance@piloteurope.com

1.4. Emergency telephone number

Telephone number : +33 (0)1 45 42 59 59

Association / Organization : ORFILA / INRS http://www.centres-antipoison.net

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable Liquid 2 H225 (WMAM-B/L/G/V, WMA-R/O)

Eye Damage / Eye Irritation 2 H319 (WMAM-B/L/G/V)

Specific target organ toxicity (Single exposure) 3 H336 (WMAM-B/L/G)

2.2. Label elements

Labeling according Regulation (EC) No 1272/2008

Hazard Pictograms



Signal word Danger

Product Name : Cartridge for V BOARD MASTER SDS No.:RI-023

Hazard statement(s)

H225 Highly flammable liquid and vapour. (WMAM-B/L/G/V ,WMA-R/O)

Page 2/7

H319 Causes serious eye irritation. (WMAM-B/L/G/V)
H336 May cause drowsiness or dizziness. (WMAM-B/L/G)

Precautionary statement(s)

Prevention

P210 Keep away from heat/Sparks/open flames/hot surfaces.-No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS No.	EC No.	Index No.	REACH Registratio n No.	% Weight	Classification (EC)No 1272/2008	Compo nent
Ethanol	64-17-5	200- 578-6	603-002	01-21194 57610-43 -xxxx	30-80	Flam Liq.2. H225	All colors
Propan-2-ol	67-63-0	200- 661-7	603-117 -00-0	01-21194 57558-25 -xxxx	4.0-41	Flam Liq.2 H225 Eye lrrit. 2 H319 STOT SE 3 H336	All colors
Propan-1-ol	71-23-8	200- 746-9	603-003	-	1.0-2.9	Flam liq. 2 H225 Eye Dam.1 H318 STOT SE3 H336	Black Violet
Carbon black	1333- 86-4	215- 609-9	Not applicable	-	4.0	Not classified	Black
Coloring material	Trade secret	Trade secret	Trade secret	Trade secret	2.0-5.0	Not classified	Except black
Additive agent	Trade secret	Trade secret	Trade secret	Trade secret	Remainder	Not classified	All colors

H318: Causes serious eye damage.

Product Name: Cartridge for V BOARD MASTER

Page 3/7

SDS No.:RI-023

4. FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation : Remove subject to ventilated fresh air. Consult physician if necessary.

Ingestion : Refer for medical attention.

Skin contact : Wash the affected area under tepid running water using a mild soap.

And refer for medical attention if irritation continues.

Eye contact : Gently rinse the affected eyes with clean water for at least 15 minutes.

And refer for medical attention if irritation continues.

First aid facilities : Ensure eyewash and water service are available.

4.2. Most important symptoms and effects, both acute and delayed

In case of skin or eye contamination treat as under First Aid Measures.

4.3. Indication of any immediate medical attention and special treatment needed

There is no specific antidote. Treat symptoms.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media : In case of fire, use water spray, foam, dry, chemical powder

or carbon dioxide.

5.2. Special hazards arising from CO_2 , CO, NO_x , and SO_x , is produced after combustion.

the substance or mixture

5.3. Advice for firefighters : None

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

: Use proper ventilation. Use eye and skin protection.

6.2. Environmental precautions

: Do not dispose of waste to the sewer.

6.3. Methods and material for containment and cleaning up

: Absorb spill with material (cloth or paper), then place in a chemical waste containers.

6.4. Reference to other sections : None

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

: Use proper ventilation.

Avoid rough handling or dropping.

Wear protective gloves / protective clothing /eye protection / face protection.

Keep out of reach of children and do not drink ink.

7.2. Conditions for safe storage, including any incompatibilities

: Store in a dry, cool, well-ventilated location.

7.3. Specific end use(s)

: Not use it except the ink for writing instruments.

SDS No.:RI-023

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Data of France.

	Limit value - Eight hours	Limit value - Short term
Ethanol	1000ppm	5000ppm
Propan-2-ol	_	400ppm

8.2. Exposure controls

: Wear protective gloves / protective clothing / eye protection / face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties				
(a) Appearance	: Black/red/Blue/Green/Orange/Violet Liquid			
(b) Odour	: Alcohol odour			
(c) Odour threshold	: No data			
(d) pH	: Not applicable			
(e) Melting point / Freezing point	: No data			
(f) Boiling point / boiling range	: 78.3 degrees Celsius (Ethanol)			
(g) Flash point	: 14.0 degrees Celsius (Ethanol)			
(h) Evaporation rate	: No data			
(i) Flammability (solid, gas)	: Flammable			
(j) Upper/lower flammability or	: None			
explosive limits				
(k) Vapor pressure	: 40hPa (at 20 degrees Celsius, Ethanol)			
(l) Vapor density	: 1.6 (at 20 degrees Celsius, Ethanol)			
(m) Relative density	: 0.81-0.85 (at 20 degrees Celsius)			
(n) Solubility(ies)	: Not applicable			
(o) Partition coefficient: n-octanol / water	: Not available			
(p) Auto-ignition temperature	: No data			
(q) Decomposition temperature	: No data			
(r) Viscosity	: 5.0-13.0 mPa·s (at 20 degrees Celsius)			
(s) Explosive properties	: No data			
(t) Oxidising properties	: No data			
9.2. Other information	: None			

10. STABILITY AND REACTIVITY

10.1. Reactivity : This material is stable.

: This material is stable. 10.2. Chemical stability

10.3. Possibility of hazardous reactions : This material is stable.

10.4. Conditions to avoid : Direct sunshine, the high temperature and

source of ignition.

10.5. Incompatible materials : Strong oxidizing agents and reducing agents.

10.6. Hazardous decomposition products : Heating can release vapours which can be ignited.

: Burning produces obnoxious and toxic fumes,

carbon oxides.

SDS No.:RI-023

11. TOXICOLOGICAL INFORMATION

Mixture: No data

11.1. Information on toxicologic	cal effects	
(a) acute toxicity	Ethanol	: LD ₅₀ 11,500 mg/kg (rat oral)
	Propan-2-ol	: LD ₅₀ 3,437 mg/kg (rat oral)
		: LD ₅₀ 4,059 mg/kg (rabbit skin)
	Propan-1-ol	: LD ₅₀ 2,695 mg/kg (rat oral)
(b) skin corrosion/	Ethanol	: 400 mg open ; MILD (rabbit skin)
irritation	Propan-2-ol	: 500 mg open ; MILD (rabbit skin)
	Propan-1-ol	: 500 mg open ; MILD (rabbit skin)
(c) serious eye damage/	Ethanol	: 100 mg/24h ; MODERATE
irritation		(rabbit eye)
	Propan-2-ol	: 100 mg/24h ; MODERATE
		(rabbit eye)
	Propan-1-ol	: 100 mg/24h ; MODERATE
		(rabbit eye)
(d) respiratory or skin sensitisation	No data available	
(e) germ cell mutagenicity	No data available	
(f) carcinogenicity	Carbon black	:IARC Class 2B
(g) reproductive toxicity	No data available	
(h) STOT-single exposure	Propan-2-ol	: May cause drowsiness or dizziness
	Propan-1-ol	: May cause drowsiness or dizziness
(i) STOT-repeated exposure	No data available	
(j) aspiration hazard	No data available	

Although carbon black is classified with 2B by IARC, it was in solution, and since it was not a granular material, it carried out the outside of classification.

12. ECOLOGICAL INFORMATION

Mixture: No data.

12.1. Toxicity	Ethanol	: LC ₅₀ - Salmo gairdneri-13,000 mg/L-96H
		EC_{50} - Daphnia magna-12,340 mg/L-48H
	Propan-2-ol	: LC ₅₀ - Fathead minnow- 11,130mg/L-96H
	Propan-1-ol	: EC ₅₀ - Daphnia magna(Water flea)-
		3,025 mg/L-48H
12.2. Persistence and	No data available	
degradability		
12.3. Bioaccumulative	No data available	
potential		
12.4. Mobility in soil	No data available	
12.5. Results of PBT and	No data available	
vPvB assessment		
12.6. Other adverse effects	No data available	

SDS No.:RI-023

13. DISPOSAL CONSIDERATIONS

- 13.1. Waste treatment methods
 - · Follow all regulations in your country.

14. TRANSPORT INFORMATION

14.1. UN number : 1993

14.2. UN proper shipping name : Flammable liquid N.O.S (Ethanol)

: 3 14.3. Transport hazard class(es) 14.4. Packing group : II

14.5. Environmental hazards : Not applicable. 14.6. Special precautions for user : Not applicable.

14.7. Transport in bulk according to Annex II of : Not applicable.

MARPOL 73/78 and the IBC Code

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Follow all regulations in your country.
- 15.2. Chemical safety assessment
 - · No data

16. OTHER INFORMATION

Hazard statement according to (EC) No 1272/2008

Precautionary Statements					
Prevention	P233	Keep container tightly closed.			
	P240	Ground / bond container and receiving equipment.			
	P241	Use explosion-proof electrical, ventilating and lighting			
		equipment.			
	P242	Use only non-sparkling tools.			
	P243	Take precautionary measures against static discharge.			
	P280	Wear protective gloves/protective clothing/eye protection/face			
		protection.			
P264		Wash hands thoroughly after handling.			
	P261	Avoid breathing mist or vapours or spray.			
Response	P303+P361	IF ON SKIN (or hair): Take off immediately all contaminated			
	+P353	clothing. Rinse skin with water.			
	P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a			
		position comfortable for breathing.			
	P337+P313	If eye irritation persists: Get medical advice and attention.			
	P312	Call a POISON CENTER or doctor if you feel unwell.			
	P370 + P378	In case of fire: Use water spray, foam, dry chemical powder or			
		carbon dioxide for extinction.			

-	D 1 4	λ Τ .	$\alpha + 1$	C	V BOARD MASTER
	Product	name ·	Cartriage	IOY.	v DUARD WASTER

oduct Name : C	SDS No.:RI-023	Page 7/7		
Storage	P403+P235	Store in a well-ventilated place.	Keep cool.	
P403+P233 Store in a well-ventilated place. Keep container tight				closed.
	P405	Store locked up.		
Disposal P501		Dispose of contents and container in accordance with all local,		
		regional, national and internati	onal regulations.	

The information here is given in good faith, but no warranty, express or implied, is made. Final determination of suitability of any material is the sole responsibility of the user.

End of SDS