



TEGERA® 8807 INFINITY



Learn more

SUPER SOFT, THIN GLOVE, CUT LEVEL D

Dexterous, thin glove with cut resistant level D, suitable for fine assembly work. 15 gg knitted with CRF® cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Protection against contact heat up to 100°C. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Extra comfortable
- Flexible
- Durable
- Good grip in oily environments

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Anatomically designed
- Reinforcement between index finger and thumb



INFINITY™



PREVENTS RISK OF

cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, sheet-metal work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

PRIMARY INDUSTRIES OF USE

pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL CRF® Technology, Glass fibre thread, Nylon, Spandex, 15 gg

GRIP DESIGN Foam grip pattern

COLOUR Black, Yellow

PAIRS PER: BUNDLE/CARTON 6/120

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUT RESISTANCE (EN ISO 13997) Cut resistance level D


CUT RESISTANCE (EN ISO 13977) TDM: 17 N

INNER MATERIAL SPECIFICATION HPPE, Nylon, Glass fibre thread, Elastane


OUTER MATERIAL SPECIFICATION Nitrile



EN 420:2003
+A1:2009



EN 388:2016
4X43D



EN 407:2004
XIXXXX



SIZE	ARTICLE NUMBER	EAN
5	8807-5	7340118328232
6	8807-6	7340118319650
7	8807-7	7340118319667
8	8807-8	7340118319674
9	8807-9	7340118319681
10	8807-10	7340118319636
11	8807-11	7340118319643

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com