

# Jigsaw

## 4350CT

720 W • 800 – 2 800 min<sup>-1</sup>

**Efficient jigsaw with tool-less blade change and adjustable speed for professionals**

An efficient 720 W jigsaw with three-stage pendulum action and tool-less blade change for professional use. Effective anti-vibration system and low noise levels. Engine speed can be adjusted between 800 and 2 800 min<sup>-1</sup> to suit the material. A stroke length of 26 mm and cutting capacity of 135 mm in wood and 10 mm in steel.



### Technical specifications

|                                         |                              |
|-----------------------------------------|------------------------------|
| Continuous Input Power 240V             | 720 W                        |
| Length of Stroke                        | 26 mm                        |
| Max. Bevel Range (Left)                 | 0 - 45 °                     |
| Max. Cutting Capacity in Wood (90°)     | 135 mm                       |
| Max. Cutting Capacity in Steel (90°)    | 10 mm                        |
| Orbital Action                          | ✓                            |
| Power Supply Cord                       | 2,5 m                        |
| Sound Power Level (L <sub>WA</sub> )    | 95 dB(A)                     |
| Sound Pressure Level (L <sub>pA</sub> ) | 87 dB(A)                     |
| Noise Uncertainty (K Factor)            | 3 dB(A)                      |
| Vibration Level, Cutting Sheet Metal    | 4,5 m/s <sup>2</sup>         |
| Weight Without Cable                    | 2,5 kg                       |
| Product Dimensions (L x W x H):         | 236 x 73 x 207 mm            |
| Max Output Power                        | 700 W                        |
| Strokes per Minute (SPM)                | 800 - 2800 min <sup>-1</sup> |
| Max. Bevel Range (Right)                | 0 - 45 °                     |

**EAN 0088381080590**

Link to product - [www.makitauk.com](http://www.makitauk.com)

### User benefits

- Tool-less blade change for fast blade installation and removal
- 3 orbital settings
- The rubber coating on the handle ensures a firm working grip
- Constant speed control maintains constant speed under load
- Variable speed control dial enables user to match the speed to the application for greater versatility



# Related products

Optional AC

193516-3

Parallel Guide



193517-1

Guide rail adapter



415524-7

Anti-splintering device



783202-0

Hex Wrench 4Mm



824809-4

Plastic carrying case



Other

User manual

Parts drawing